



CURVA PLANA / CURVA VERTICAL INTERIOR / CURVA VERTICAL EXTERIOR 90 GRADOS ZMX 3.1/4

				ALU						
	A	P	R	CP		VI		VE		
	pulgadas	pulgadas	polgadas	REF	Kg/ud	REF	Kg/ud	REF	Kg/ud	
<p>CP'R-90 ZMX 'A'x3.1/4 AL</p>	4	3.1/4	8	2/7583	0,66	2/7623	1,12	2/7663	1,12	<p>CP'R-90 ZMX 'A'x3.1/4 AL</p>
	6	3.1/4	8	2/7584	0,75	2/7624	1,15	2/7664	1,15	
	9	3.1/4	8	2/7585	0,88	2/7625	1,2	2/7665	1,2	
	12	3.1/4	8	2/7586	1,01	2/7626	1,25	2/7666	1,25	
	16	3.1/4	8	2/7587	1,31	2/7627	1,32	2/7667	1,32	
	18	3.1/4	8	2/7588	1,42	2/7628	1,35	2/7668	1,35	
	20	3.1/4	8	2/7589	1,52	2/7629	1,38	2/7669	1,38	
	24	3.1/4	8	2/7590	1,72	2/7630	1,45	2/7670	1,45	
	30	3.1/4	8	2/7591	2,28	2/7631	1,54	2/7671	1,54	
	36	3.1/4	8	2/7592	2,64	2/7632	1,64	2/7672	1,64	
<p>VI'R-90 ZMX 'A'x3.1/4 AL</p>	4	3.1/4	12	2/9008	0,81	2/9078	2,15	2/9028	1,94	<p>VI'R-90 ZMX 'A'x3.1/4 AL</p>
	6	3.1/4	12	2/9009	0,95	2/9079	2,2	2/9029	1,99	
	9	3.1/4	12	2/9010	1,11	2/9080	2,27	2/9030	2,07	
	12	3.1/4	12	2/9011	1,26	2/9081	2,34	2/9031	2,14	
	16	3.1/4	12	2/9012	1,46	2/9082	2,44	2/9032	2,24	
	18	3.1/4	12	2/9013	1,72	2/9083	2,49	2/9033	2,28	
	20	3.1/4	12	2/9014	1,84	2/9084	2,54	2/9034	2,33	
	24	3.1/4	12	2/9015	2,08	2/9085	2,63	2/9035	2,43	
	30	3.1/4	12	2/9016	2,68	2/9086	2,78	2/9036	2,58	
	36	3.1/4	12	2/9017	3,09	2/9087	2,92	2/9037	2,72	
<p>VE'R-90 ZMX 'A'x3.1/4 AL</p>	4	3.1/4	24	2/8908	1,38	2/9088	5,37	2/9038	4,72	<p>VE'R-90 ZMX 'A'x3.1/4 AL</p>
	6	3.1/4	24	2/8909	1,52	2/9089	5,43	2/9039	4,78	
	9	3.1/4	24	2/8910	1,72	2/9090	5,53	2/9040	4,88	
	12	3.1/4	24	2/8911	1,92	2/9091	5,63	2/9041	4,98	
	16	3.1/4	24	2/8912	2,33	2/9092	5,76	2/9042	5,11	
	18	3.1/4	24	2/8913	2,48	2/9093	5,82	2/9043	5,17	
	20	3.1/4	24	2/8914	2,63	2/9094	5,89	2/9044	5,24	
	24	3.1/4	24	2/8915	2,93	2/9095	6,02	2/9045	5,37	
	30	3.1/4	24	2/8916	3,63	2/9096	6,21	2/9046	5,56	
	36	3.1/4	24	2/8917	4,13	2/9097	6,41	2/9047	5,76	

Para montar los accesorios se usan 2 juntas de unión de la altura correspondiente. Se necesitan 12 tornillos referencia 2/5392 en i304 (producto embalado en bolsas de 100)