


Type:	Pivot swivel patch panel	
Ref:	PSR-B0-x, see ordering information	REV: 1.1
Date:	20.06.2017	At
Modification:	12.04.2019	DP

## Distribution solutions

### Pivot swivel patch panel with side access **PSR-B0**



#### INTRODUCTION:

Pivot swivel patch panel PSR-B0 type, 1U or 2U height, is basic mounting block for fiber management system in patch panel holder. Available in version routing on the left or right side, so it offers well accessibility to trays and patching cords on both sides. It minimizes and protect patch cords cables movement inside patch panels.

Patch panel PSR-B0 is equipped with holder for pivot swivel splice trays SCM-B with maximum capacity of 4 splice trays in the 1U height and 8 splice trays in the 2U height.

#### APPLICATION:

Fiber optics interchanges points;  
Distribution network;  
Server room;

#### FEATURES & BENEFITS:

Metal casing with anticorrosive protection;  
Cable bushings in back part of line cables;  
Cable bushing in front part of patchcords;  
Capacity up to:  
- 48 fibers in 1U;  
- 96 fibers in 2U;  
Patch panel installation on back or front rack profile;  
Panel available in rotating left or right side of patch panel (depends on version);  
Possibilities of termination cables on side or back of patch panel;  
Hinged flap of patch panel protects patchcords from damages.

#### TECHNICAL SPECIFICATION:

Technical data	PSR-B0-01 / PSR-B0-B1	PSR-B0-02 / PSR-B0-B2
Height	1U	2U
Width	19"	19"
Depth [mm]	315	315
Max. number of fibers	48	96
Max. number of splices	48	96
Max. number of splice trays	4	8
Max. line cable diameter [mm]	12	12
Operation temperature	-20°C - +50°C	
Casing material	powder painted steel	

Type:	Pivot swivel patch panel	
Ref:	PSR-B0-x, see ordering information	REV: 1.1
Date:	20.06.2017	At
Modification:	12.04.2019	DP

## Distribution solutions



View of 1U patch panel



View of 2U patch panel



2U Patch panel with embeddable RT-01 tube separator



1U and 2U Patch panel with embeddable PS-TH-12-05 tube separator

### ORDERING INFORMATION:

**PSR-B0-XX-A-BC-DDEFG-HHIJKLL-MM0-P**

Ordering syntax for equipped PSR-B0

**XX – Height variant**

01 – 1U (grey RAL7035)  
02 – 2U (grey RAL7035)  
B1 – 1U (black RAL9005)  
B2 – 2U (black RAL9005)

**A - Shelf opening direction:**

R – right  
L – left

**B – Splice tray quantity**

4, 8

**C – Cassette type**

1 – SCM-B-12H

**DD – Adapters qty**

48, 96

**E – Adapter class**

1 – Standard One-Piece  
2 – Premium One-Piece with internal shutter

**F – Adapter type (flangeless only)**

1 – SC  
2 – SCA  
3 – E2000  
4 – E2000 APC

**G – Transmission**

1 – SM  
2 – MM (beige @SC, black @E2000)  
3 – MM OM3 (aqua @SC)  
4 – MM OM4 (violet @SC)

**HH – Pigtails quantity**

48, 96

**I – Fiber type**

A – G652D  
B – G.655  
C – G.656  
D – G.657A1  
E – G.657A2  
F – G.657B3

Type:	Pivot swivel patch panel	
Ref:	PSR-B0-x, see ordering information	REV: 1.1
Date:	20.06.2017	At
Modification:	12.04.2019	DP

## Distribution solutions

### J – Connector type

G – G.657B3+  
H – MM OM1  
I – MM OM2  
K – MM OM3  
L – MM OM4  
1 – SC  
2 – SCA  
3 – E2000  
4 – E2000 APC  
G – Gold  
T – Titanium

### K – Pigtailed grade

### LL – Colour identification:

01 – for pigtailed with yellow 0.9 mm buffer  
02 – for pigtailed with orange 0.9 mm buffer  
03 – T TELECOM (acc. to IEC60304)  
04 – T1 TELECOM (acc. to 60304/tab. 3 & ZN-11/TPSA-005-02)  
05 – T2 TELECOM (acc. to EIA 598A)  
06 – D DATACOM (acc. to DIN VDE 0888 & IEC 60304)  
07 – D1 DATACOM (acc. to IEC 60304, TIA/EIA 598-A, TIA/EIA 598-C)  
08 – for pigtailed with aqua 0.9 mm buffer

### MM – Splice sleeve quantity

48, 96

### O – Splice sleeve type

1 – 45 mm

### P – Cable tube divider

0 – without  
1 – with PS-TH-12-05 mounted

#### Important notice

Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Term of Sale of the selling Fibrain subsidiary.